

Declaration of Performance



DoP Number	GR-1018-001
1 Unique identification code of the product-type	FIBRANxps FABRIC
2 Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR	FABRIC 60
3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Thermal insulation for buildings XPS-EN 13164-T3-CS(10Y)300-DS(TH)-TR400-WL(T)1,5
4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)	FIBRAN S.A. 56010, Thessaloniki, Greece
5 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not relevant
6 System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V.	AVCP - System 3
7 In case of the declaration of performance concerning a construction product covered by a harmonised standard (Name and identification number of the notified body, if relevant).	FIW No. 0751

Harmonised standard EN 13164:2008

8 Declared performance

Essential characteristics	Performance	Unit	Declared performance
Thermal Resistance	Thickness	d_N [mm]	60
	Thickness Class	T	T3
	Thermal Resistance	R_D [m ² K/W]	1,80
	Thermal Conductivity	λ_D [W/m K]	0,033
Reaction to fire	Reaction to fire	Euroclass	E
Release of Dangerous Substances	Release of Dangerous Substances		NPD
Acoustic absorption index	Sound absorption		NPD
Continuous glowing combustion	Continuous glowing combustion		NPD
Water Permeability	long term water absorption by total immersion	WL(T) [vol. %]	1,5
	long term water absorption by diffusion	WD(V) [vol. %]	NPD
Water vapour permeability	Water vapor diffusion resistance factor	MU	50
Compressive strength	Compressive stress or compressive strength	CS(10/Y) [kPa]	200
Tensile/Flexural strength	Tensile Strength perpendicular to faces	TR [kPa]	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	Reaction to fire	Euroclass	E
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal Resistance	R_D [m ² K/W]	1,80
	Thermal Conductivity	λ_D [W/m K]	0,033
	freeze-thaw resistance after long term water diffusion test	FTCD	NPD
	freeze/thaw resistance after long term water absorption by total immersion	FTCI	NPD
	dimensional stability under specified temperature and humidity conditions	DS	NPD
	Deformation under specified compressive load and temperature conditions	DLT	NPD
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	CC (2/1,5/50)	NPD

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Name	Stella Chadiarakou
Function	R&D -Quality Assurance Manager
Place	Thessaloniki
Date	01/07/2013
Signature	

This product contains Hexabromocyclodecane (declaration according to CPR requirement Article 6 Paragraph 5)