

# Declaration of Performance



## DoP Number

- 1 Unique identification code of the product-type
- 2 Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR
- 3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer
- 4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)
- 5 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)
- 6 System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V.
- 7 In case of the declaration of performance concerning a construction product covered by a harmonised standard (Name and identification number of the notified body, if relevant).

GR-2098-002

FIBRANgeo BP-50-AL

BP-50-AL

Thermal Insulation of Buildings (ThIB)

FIBRAN S.A. 56410, Thessaloniki, Greece

not relevant

AVCP - System 1

FIW No. 0751 (Forschungsinstitut für Wärmeschutz e.v München)

FIW No. 0751 (Forschungsinstitut für Wärmeschutz e.v München) performed under system (description of the third party tasks as set out in Annex V), and issued (certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports - as relevant).

Harmonised standard

EN 13162:2012

## 8 Declared performance

Essential characteristics	Performance	Abreviation	Unit	Declared performance
Reaction to fire	Reaction to fire	RtF	Euroclass	A1
Release of Dangerous Substances	Release of Dangerous Substances			NPD
Acoustic absorption index	Sound absorption			NPD
Impact Noise Transmission Index	Dynamic stiffness	s'	MN/m <sup>2</sup>	32
	Thickness	d <sub>L</sub>	mm	40
	Compressibility	c	mm	2
	Air flow resistivity	AF <sub>r</sub>	kPa.s/m <sup>2</sup>	60
Direct airborne sound insulation index	Air flow resistivity	AF <sub>r</sub>	kPa.s/m <sup>2</sup>	60
Continous glowing combustion	Continous glowing combustion			NPD
Thermal Resistance	Thermal Resistance	R <sub>D</sub>	m <sup>2</sup> K/W	see below table
	Thermal Conductivity	λ <sub>D</sub>	W/m K	0,038
	Thickness	d <sub>N</sub>	mm	30-300
	Thickness Class	T	Class	T7
Water Permeability	Short term Water absorption	W <sub>p</sub>	kg/m <sup>2</sup>	<1
	Long term water absorption	W <sub>lp</sub>	kg/m <sup>2</sup>	<3
Water vapour permeability	Water vapour transmission	μ		NPD
		Z	m <sup>2</sup> hPa/mg	>150
Compressive strength	Compressive stress or compressive	CS	kPa	50
	Point Load	F <sub>p</sub>	N	600
Durability of reaction to fire against heat, weathering, ageing/degradation	Reaction to fire	RtF	Euroclass	A1
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal Resistance	R	m <sup>2</sup> K/W	see below table
	Thermal Conductivity	λ	W/m K	0,038
	Durability Characteristics	d	mm	30-300
Tensile/Flexural strength	Tensile Strength perpendicular to faces	TR	kPa	15
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	Xct, Xt	mm	NPD

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Thickness	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	180	200
R (m <sup>2</sup> K/W)	0,50	0,75	1,05	1,30	1,55	1,80	2,10	2,35	2,60	2,85	3,15	3,40	3,65	3,90	4,20	4,70	5,25

Name  
Function  
Place  
Date  
Signature

Stella Chadiarakou  
R&D - Quality Assurance Manager  
Thessaloniki  
01/11/2015