

DECLARATION OF PERFORMANCE



DoP Number

GR-5002-001

1. Unique identification code of the product-type:

FIBRANskin SMART

2. Intended use/es:

Application: Plastic and rubber vapour control layers
- EN 13984:2013

3. Manufacturer:

FIBRAN S.A. 56410, Thessaloniki, Greece

4. Authorised representative:

5. System/s of AVCP:

System 3

6a. Harmonised standard:

EN 13984:2013

Notified body/ies:

KIWA TBU DE (NB 0799)

7. Declared performance/s:

EN 13984:2013

8. Essential characteristics

Performance

PROPERTY	METHOD	UNITS	NOMINAL	MINIMUM	MAXIMUM
Product designation according to EN 13984	-	-	B	-	-
Water vapour transmission (sd)	EN 1931 (23-0/75)	m	13	8	18
Density of water vapour flow rate (g)	EN 1931 (23-0/75)	kg / (m ² s)	3,16E-8	5,14E-8	2,28E-08
Durability (exposure to artificial ageing)					
Water vapour transmission properties	EN 1931	pass / no pass	(+)	-	-
Reaction to fire	EN ISO 11925-2	class	E	-	-
Maximum tensile force (MD)	EN 12311-2	N/50mm	390	330	-
Elongation at max. tensile force (MD)	EN 12311-2	%	16	12	-
Maximum tensile force (XD)	EN 12311-2	N/50mm	380	330	-
Elongation at max. tensile force (XD)	EN 12311-2	%	19	14	-
Resistance to tearing MD (nail shank)	EN 12310-1	N	75	45	-
Resistance to tearing XD (nail shank)	EN 12310-1	N	65	40	-
Resistance to impact	EN 12691	mm	(+)	-	-
Joint strength	EN 12317-2	N/5cm	-	280	-
Durability (against alkali)					
Elongation at max. tensile force (MD)	EN 12311-2	pass / no pass	pass	-	-
Elongation at max. tensile force (XD)	EN 12311-2	pass / no pass	pass	-	-

(+): No Performance Determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Stella Chadiarakou

R&D - Quality Assurance Manager

Thessaloniki

1/2/2022