



TECHNICAL DATA SHEET

04/02/2022

GLASSWOOL BUILDING BLANKET GF 1330-A

REV : 0

Properties	Symbol	Unit	Description	Tolerance	Standard
Material	-	-	Glass Wool	-	EN 13162
Density	ρ	kg/m ³	13	+/-10%	-
Width	W	mm	1200	+/-1,5%	EN 822
Length	L	mm	24000	+/-2%	EN 822
Thickness	t	mm	30	T1	EN 823
Facing	-	-	Alufoil	-	-
Fire Behaviour	-	-	C-s1,d0	-	EN 13501-1
Thermal Conductivity (10 °C) Declared	λ	W/mK	0,040	-	EN 12667 EN 12939
Thermal Resistance (10 ⁰ C)	R	m ² K/W	0,75	-	-
Max. Service Temperature	-	°C	250#	-	-
Specific Heat *	c	kJ/(kg.K)	0,84	-	EN 12524
Packaging Material	-	-	PE Film or bag	-	-
Application Area	For general thermal and acoustical insulation applications.				
Remarks	* Maximum service temperature of Alufoil side is 90 °C.				

* Literature Value.

Izocam Glasswool Products are manufactured under the licence of Saint Gobain Isover.
Izocam Glasswool Products are manufactured in İZOCAM Tarsus Glasswool Plant having ISO 9001, ISO 14001 and ISO 45001 Management System Certificates.

